

PA 1234558

PCT IB04/051739.

REC'D 18 OCT 2004

WIPO PCT

THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

October 08, 2004

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE UNDER 35 USC 111.

APPLICATION NUMBER: 60/584,833

FILING DATE: June 30, 2004

**PRIORITY
DOCUMENT**
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

By Authority of the
COMMISSIONER OF PATENTS AND TRADEMARKS



P. R. Grant
P. R. GRANT
Certifying Officer

22713 U.S. PTO

PTO/SB/16 (10-01)
Approved for use through 10/31/2002. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PROVISIONAL APPLICATION FOR PATENT COVER SHEET

This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53(c).

Express Mail Label No.

ER 556413488 US

22713 U.S. PTO
0651-0032

063004

INVENTOR(S)					
Given Name (first and middle [if any])	Family Name or Surname	Residence (City and either State or Foreign Country)			
Vladimir	PEKAR	HAMBURG, GERMANY			
Michael	KAUS	HAMBURG, GERMANY			
Todd	MC NUTT	VERONA, WISCONSIN			
<input type="checkbox"/> Additional inventors are being named on the _____ separately numbered sheets attached hereto					
TITLE OF THE INVENTION (500 characters max)					
METHOD AND DEVICE FOR PLANNING A RADIATION THERAPY					
Direct all correspondence to: CORRESPONDENCE ADDRESS					
<input type="checkbox"/> Customer Number		Type Customer Number here		Place Customer Number Bar Code Label here	
OR					
<input checked="" type="checkbox"/> Firm or Individual Name		Wayne M. Serra			
Address		Philips Intellectual Property & Standards			
Address		595 Miner Road			
City		Cleveland	State	Ohio	ZIP 44143
Country		US	Telephone	440-483-2373	Fax 440-483-4874
ENCLOSED APPLICATION PARTS (check all that apply)					
<input checked="" type="checkbox"/> Specification Number of Pages				<input type="checkbox"/> CD(s), Number	
<input checked="" type="checkbox"/> Drawing(s) Number of Sheets				<input type="checkbox"/> Other (specify)	
<input type="checkbox"/> Application Data Sheet. See 37 CFR 1.76					
METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT					
<input type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27.				FILING FEE AMOUNT (\$)	
<input type="checkbox"/> A check or money order is enclosed to cover the filing fees					
<input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge filing fees or credit any overpayment to Deposit Account Number:		14-1270		\$160.00	
<input type="checkbox"/> Payment by credit card. Form PTO-2038 is attached.					
The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.					
<input checked="" type="checkbox"/> No.					
<input type="checkbox"/> Yes, the name of the U.S. Government agency and the Government contract number are: _____					

Respectfully submitted,

SIGNATURE

Date 06/30/2004

REGISTRATION NO.
(if appropriate)
Docket Number:

51,138

PHUS030326USP

TYPED or PRINTED NAME Wayne M. Serra

TELEPHONE 440-483-2373

USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

This collection of information is required by 37 CFR 1.51. The information is used by the public to file (and by the PTO to process) a provisional application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the complete provisional application to the PTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, Washington, D.C. 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Box Provisional Application, Assistant Commissioner for Patents, Washington, D.C. 20231.

Method and Device for Planning a Radiation Therapy

Technical Field

The disclosed devices and methods relate to the field of radiation therapy planning (RTP). In particular, the disclosed devices and methods relate to a method of planning a radiation therapy, to a radiation therapy planning device and to a computer program for a radiation therapy planning device.

5

Background of the Disclosed Devices and Methods

Radiation Therapy Planning (RTP) may be carried out using a computed tomography (CT) image of a patient that is acquired prior to an actual radiation treatment of the patient. Radiation planning systems usually require data regarding contours of the target volume of a patient containing, for example, a tumour, and of the healthy, at-risk organs which have to be spared during dose delivery. Using this contour data, which are delineated by manual or semi-automatic contouring methods, a dose distribution is calculated for the structures of interest and the optimal parameters of radiation treatment beams are computed.

15

Dose calculations can lose accuracy during the treatment process because of shape and position changes of the organs occurring from certain physiological processes, such as bladder filling, increases or decrease of the tumour sizes, breathing, heartbeat, or other physiological processes.

20

Summary of the Disclosure

It is an object of the presently disclosed devices and methods to provide for an improved radiation therapy planning.

25

A method of planning a radiation therapy is provided, wherein a dose distribution for a target volume comprising an object of interest is determined on the basis of a first image. Then, at least one of a shape and position variation of an object of interest in the target volume is determined on the basis of the first image and a second image. The dose distribution is then adjusted on the basis of the at least one of shape and position variation

of the object of interest. The first and second images were taken at different points in time of a radiation treatment.

An initial dose distribution may be determined on the basis of a first image, which is, for example, taken before the start of the actual radiation treatment. Then, for example, after a plurality of dose deliveries or after a certain time or before a subsequent dose delivery, a second image is taken. Shape and/or position changes of the object of interest, such as the organs, between the first and second images, are determined. Then, the distribution is adjusted on the basis of the shape and/or position variation.

A radiation therapy planning may be provided allowing for an improved dose estimation for the target volume. This allows for an improved tumour control. Further, the dose calculation may be automatically adjusted taking into account changes to a patient's anatomy.

A first surface mesh is applied to the object of interest in the first image and is adapted to the surface of the object of interest, which results in a second surface mesh. This second surface mesh is applied to the object of interest in the second image and is adapted to the surface of interest in the second image. This adaptation of the second surface mesh to the object of interest results in a third surface mesh. Then, a difference between the second surface mesh and the third surface mesh is determined.

A method is provided for determining the contours of the object of interest in the target volume. By using such a surface mesh adaptation, an automatic organ delineation may be provided.

A volumetric model of the object of interest, such as one or more organs, is determined on the basis of the second surface mesh. Then, the volumetric model is deformed on the basis of the difference, for example, shape and/or position changes of the organs between the first image and the second image. The deformation of the volumetric model results in a deformed volumetric model. The shape and/or variation(s) of the object of interest is interpolated into the volumetric model. The difference, i.e., the shape and/or

position variation of the object of interest is used as a boundary condition for the deformation of the volumetric model. At least one of shape and position variation of the object of interest is determined on the basis of the deformed volumetric model.

5 The dose calculation is adjusted, taking into account changes of the object of interest between the first and second image, for example, changes in the patient's anatomy occurring during the time between the first and second images.

10 A model of the biomechanical tissue-properties is taken into account for the deformation of the volumetric model. A combination of surface meshes and a biomechanical, volumetric model is used for a very accurate and automatic radiation therapy planning. In particular, the adapted surface meshes are used as a boundary condition for the deformation of the biomechanical, volumetric model.

15 A shape and/or position variation of the object of interest is determined. The object of interest may, for example, contain a plurality of organs, each having different mechanical characteristics. The biomechanical model takes these different mechanical characteristics into account when the shape and/or position variation of the object of interest determined on the basis of the surface meshes is used to deform the biomechanical,
20 volumetric model accordingly. This allows a treating individual to more accurately take into account non-rigid changes occurring in the patient's anatomy during the radiation treatment. The first and second images may be computed tomography (CT) images. Alternatively, the procedure is possible with magnetic resonance imaging (MRI) images.

25 A radiation therapy planning device is provided comprising a memory for storing the first and second images and a processor performing a dose distribution adjustment on the basis of at least one of a shape and position variation of the object of interest between the first image and the second image. A radiation therapy planning device may be provided allowing for a fast and accurate radiation therapy planning which may be
30 performed automatically. Changes in the patient's anatomy are taken into account for determining the dose distribution.

A computer program is provided for a radiation therapy planning device which allows for an automatic dose distribution determination by a combination of surface meshes applied to the object of interest in at least two subsequent images. By such a combination of a segmentation and a registration, an improved radiation therapy planning may be provided which may allow to reduce a dose applied to healthy (risk) organs. This computer program may be written in any suitable programming language; such as C++ and may be stored on a computer-readable device, such as a CD-ROM. However, the computer program may also be presented over a network, such as the Internet, from which it may be downloaded or run.

Brief Description of the Drawings:

Devices and methods related to planning a radiation therapy for a patient are disclosed and discussed with reference to the following drawings:

15

Figure 1 is a schematic representation of a radiation therapy planning device adapted to execute a method as disclosed herein.

Figure 2 is a flow diagram of a method of radiation therapy planning.

20

Detailed Description

Figure 1 shows a simplified schematic representation of a radiation therapy planning device. In Figure 1, a Central Processing Unit (CPU) 1 is configured to execute instructions to carry out a method related to radiation therapy planning. CPU 1 may be a general purpose processor such as that found in a typical personal computer, or it may be an application-specific integrated circuit (ASIC). The instructions executed by CPU 1 assist a user in the planning of a radiation therapy with respect to an object of interest in a target volume. The target volume is usually an area within a patient containing a cancerous tumour or other structure that will be irradiated as part of the therapy being planned.

30

The target volume may comprise a plurality of other, smaller objects, such as different organs such as the bladder, the heart, or another organ. Usually, in cases where a

radiation therapy is performed with respect to such target volumes, a tumour is located between or close to such organs. The object of most radiation therapies is usually to focus dosages of radiation onto the tumour while minimizing exposure to healthy at-risk organs adjacent to the tumour.

5

The CPU 1 is connected to a memory 2 for storing images. Memory 2 can be volatile memory such as dynamic random-access memory (DRAM), or a non-volatile memory device such as Flash memory or a disk drive. Other suitable devices capable of storing information for later retrieval and use may be used as the memory 2. In particular, 10 in the memory 2, there are stored a first image taken at a first point in time of a radiation therapy process and a second image taken at a subsequent point in time. For example, the first image may be taken before the start of the radiation treatment. An initial radiation dose distribution is determined on the basis of information contained in this first image. Then, during the radiation treatment, for example, after a plurality of radiation treatments 15 or before another immediate radiation treatment, a second image is created. Variations in the patient's anatomy, such as shape and/or position changes of the organs in the target volume, are determined from a comparison of the first image and the second image and the dose distribution is automatically adjusted to take into account noted changes in the patient's anatomy.

20

As may be taken from Figure 1, the processor may, furthermore, be connected by a bus system 3 to a plurality of peripheral devices or input/output devices which are not depicted in Figure 1. For example, the CPU 1 may be connected to a magnetic resonance (MR) device, an ultrasonic scanner, a plotter, a printer or other appropriate device via the 25 bus system 3. Preferably, for radiation therapy planning, the CPU 1 is connected to a CT scanner that acquires the first and second images. More than two images may be used if necessary or desirable.

The CPU 1 is operatively connected to a display, such as a computer screen 4 for 30 outputting the initial dose distribution and/or the adjusted dose distribution in a human-readable format. Furthermore, an input device such as keyboard 5 may be provided and operatively connected to the CPU 1, by which a user or operator may interact with the

therapy planning device depicted in Figure 1 or may input data necessary or desired for the radiation therapy planning.

Figure 2 is a flow diagram of a method of operating the radiation therapy planning device depicted in Figure 1. The disclosed method of planning a radiation therapy may be embodied in a computer program, which may be written in any suitable programming language, such as C++ and may be stored on a computer-readable medium, such as a CD-ROM. However, the computer program according to the present invention may also be presented over a network, such as the Internet, from which the program may be downloaded.

The disclosed method takes into account the possibility that a dose distribution that was initially determined on the basis of a CT image taken before the actual start of the radiation therapy may need to be adjusted to accommodate changes in shape or position of organs due to certain physiological processes, for example, bladder filling, increase or decrease of the tumour size, breathing, heartbeat, or another process. Ideally, the dose distribution is individually adjusted for each day of treatment. The dose calculation is automatically adjusted taking into account changes in the patient's anatomy from one day to the next. For this adjustment, new CT images should be taken for each day of treatment.

20

In Figure 2, two CT images are used for adjusting the dose distribution. The first CT image is referred to as initial CT image 12 and the second image is referred to as new CT image 14. Preferably, the initial CT image 12 is taken before the start of the radiation therapy treatment and new CT image 14 is then taken during the treatment process, for example, right before a subsequent radiation treatment.

25

Boundaries of a patient's organ structures in the target volume are delineated. The delineation of the organ boundaries in the initial CT image 12 may be performed manually or semi-automatically. Preferably, 3D surface models are used for performing an automated organ boundary delineation. A suitable process for performing a delineation is described in "Shape Constrained Deformable Models for 3D Medical Image Segmentation" by J. Weese et al, Proc. Information Processing in Medical Imaging (IPMI

30

'01), at pages 380-387, Los Angeles, CA, USA, June 2001, which is incorporated by reference.

In accordance with the application of 3D surface models, a surface mesh, such as a triangular mesh, is applied to the organs in the initial CT image 12. This process is sometimes referred to as adaption. It should be noted that instead of triangular meshes, it is also possible to use simplex or polygonal meshes or other suitable surface or shape models. Then, this surface mesh is adapted to the surface of the organs in the initial CT image 2 by energy minimization.

A deformable model is represented by a mesh. The mesh includes V vertices with coordinates x_i and T triangles. An iterative process adapts the mesh to an image. Each iteration includes a step to detect a surface and a step to reconfigure the mesh. The reconfiguration is accomplished by minimizing the equation

$$E = E_{ext} + \alpha E_{int}.$$

E_{ext} represents external energy. This drives the mesh toward surface patches previously detected. E_{int} represents internal energy. Internal energy restricts the flexibility of the mesh. α provides a weight on the relative influence of each term.

To detect a surface, a search is performed along the triangle normal n_i to find the point \tilde{x}_i (\tilde{x} -bar sub i) with a combination of features that includes $F_i(\tilde{x}_i)$ and distance δ_j to the triangle's center \hat{x}_i (\hat{x} -caret sub i) such that:

$$\tilde{x}_i = \hat{x}_i + n_i \delta \arg \max_{j=-l, \dots, l} \{F_i(\hat{x}_i + n_i \delta j) - D \delta^2 j^2\}$$

The profile length of the search is represented by l , δ is the distance between two successive points, and D controls the weighting of the distance information and feature value. A feature that can be used is

$$F_i(x) = \pm n_i^t g(x) \frac{g_{max}(g_{max} + \|g(x)\|)}{(g_{max}^2 + \|g(x)\|^2)}$$

where the function $g(x)$ is the image gradient at point x .

External energy represented as

$$E_{ext} = \sum_{i=1}^T w_i (\tilde{x}_i - \hat{x}_i)^2, \quad w_i = \max\{0, F_i(\tilde{x}_i) - D(\tilde{x}_i - \hat{x}_i)^2\}$$

can be used. In this case, detected surface points directly attract the triangle centers of the mesh. To diminish the influence of attraction to false object boundaries, which may be frequently detected at the beginning of the adaption process, centers of the triangles can be attracted by planes that are perpendicular to the image gradient at \tilde{x}_i (x-tilde sub i):

$$E_{ext} = \sum_{i=1}^T w_i \left(\frac{g(\tilde{x}_i)}{\|g(\tilde{x}_i)\|} (\tilde{x}_i - \hat{x}_i) \right)^2$$

Internal energy is introduced into the shape model that is represented by a mesh of triangles such that

$$m_i = m_i^0 + \sum_{k=1}^M p_k m_i^k; \quad i = 1, \dots, V.$$

where m_i^0 represents vertex coordinates of the mean model. Variation of the coordinates associated with the M eigenmodes of the model is represented by m_i^k .

Weights of the eigenmodes are represented by p_k . Difference vectors for the deformable model and the shape model are then compared with deviation penalization:

$$E_{int} = \sum_{i=1}^V \sum_{j \in N(i)} \left(x_i - x_j - sR \left(m_i^0 - m_j^0 + \sum_{k=1}^M p_k (m_i^k - m_j^k) \right) \right)^2$$

where $N(i)$ contains the neighbours of vertex i .

After or parallel to the determination of a surface mesh representing the shape and/or position of the organs in the initial CT image 12, a delineation of the boundaries of these organs is performed in the new CT image 14. Preferably, the segmentation result of the initial CT image, the surface mesh adapted to the organ surfaces in the initial CT image 12, is used as a starting mesh in the new CT image 14. Then, this starting mesh is adapted to the organ surfaces of the organs in the new CT image 14 by energy minimization as described above.

10

After the adaptation of the surface mesh to the organ surfaces in the new CT image 14, two surface meshes are known representing the organ surfaces in the initial CT image 12 and in the new CT image 14. The first mesh representing the organ surfaces in the initial CT image 12 is referred to in Figure 2 as surface1 and the second mesh representing the surfaces of the organs in the new CT image 14 is referred to surface2 in Figure 2. In a subsequent step, a difference between the surface1 and the surface2 is determined. In other words, correspondences between the surface1 and surface2 are determined. For this, the initial CT image 12 and the new CT image 14 or the surface1 and surface2 are brought into a common co-ordinate system. Because surface1 and surface2 were determined by using the same surface model, point correspondences between surface 1 and surface 2 may be determined easily.

20

A volumetric mesh is generated from the surface1 in the initial image. This volumetric mesh is now deformed using the point correspondences obtained from the comparison of surface1 and surface2. The deformation of the volumetric mesh is determined by taking into account mechanical properties of the organs, by using one or more biomechanical models. The use of biomechanical models is, for example, described in D. Yan et al, "A Method for Calculating Dose in a Deforming Organ," Int. J. Radiat. Oncol., Biol., Phys., 44, pages 665-675, 1999, which is hereby incorporated by reference.

30

An example for a simple and efficient biomechanical model is described in the following: Let V be a 3D domain occupied by the organ of interest and S be the organ boundary. A boundary value problem describing a linear elastic deformation of the organ can be formulated as:

5

$$\begin{cases} \int_V A(u) = f(x) & \text{in } V, \\ u(x) = \hat{u}(x) & \text{on } S. \end{cases}$$

In the above formula, $A(u)$ denotes the operator of linear elasticity, as, for example, described in P. G. Ciarlet, "Mathematical Elasticity, Volume 1: Three-Dimensional Elasticity, volume 20 of Studies in Mathematics and its Applications." North-Holland, Amsterdam, 1988, which is hereby incorporated by reference. $f(x)$ are the applied forces. $u(x)$ denotes the displacement field, where $\hat{u}(x)$ are the prescribed displacements on the boundary determined by using the surface meshes. A discretization of the above formula on the volumetric mesh by the finite element method results in a linear system of equations. Prescribed displacements can be included into the system as boundary conditions to constrain the resulting volumetric deformation. According to an aspect of the present invention, these boundary conditions correspond to the point correspondences between the surface1 and surface2.

Elastic properties of particular tissues can be assigned to individual tetrahedra in the 3D mesh to more exactly simulate the elastic behaviour of an organ or organs. If the organ deformation is large and cannot be adequately described by the linear model, a non-linear elastic model in the form of incremental deformation may be applied.

As a result, advantageously, displacements of individual nodes inside the organ may be computed. During radiation treatment, dose estimation in the volume of interest can be performed taking into account variations or changes of the patient's anatomy based on these computed displacements. This estimation is then used to predict the dose delivery and helps to correct the initial treatment plan.

30

As described above, a combination of a segmentation and a registration is applied to take variations in the patient's anatomy during the radiation treatment into account to adjust the dose distribution and dose delivery estimation. This is achieved by combining a surface matching method with a biomechanical, volumetric model. In particular, the result
5 of the surface method is used as boundary condition for the biomechanical, volumetric model.

Advantageously, due to the above method, the dose delivery during the treatment process may be monitored. For each point in time, where an image was taken, due to the
10 above method, the precise dose distribution can be determined. In other words, for each relevant point in time of the treatment, and for each point of interest in the target volume (risk organs) the dose delivered can be determined. This may be done by summing the dose during each dose delivery to respective points.

15 The invention disclosed herein is defined by the claims read by a person of ordinary skill in the art in light of the disclosures made in the specification. Modifications of and alterations to the materials disclosed herein will occur to others upon reading and understanding of the preceding detailed description. It is intended that the invention be construed as including all such modifications and alterations insofar as they come within
20 the scope of the appended claims or the equivalents thereof.

We claim:

1. A method of planning a radiation therapy, the method comprising the steps of:
 - determining a dose distribution for a target volume on the basis of a first image;
 - determining at least one of shape and position variation of an object of interest in the target volume between the first image and a second image; and
 - adjusting the dose distribution on the basis of the at least one of shape and position variation;
 - wherein the first and second images were taken at different points in time of a radiation treatment process.
2. The method of claim 1, further comprising the steps of:
 - applying a first surface mesh to the object of interest in the first image;
 - performing a first adaptation of the first surface mesh to a surface of the object of interest in the first image resulting in a second surface mesh;
 - applying the second surface mesh to the object of interest in the second image;
 - performing a second adaptation of the second surface mesh to the surface of the object of interest in the second image resulting in a third surface mesh; and
 - obtaining a difference between the second surface mesh and the third surface mesh.
3. The method of claim 2 further comprising the steps of:
 - generating a volumetric model of the object of interest on the basis of the second surface mesh; and
 - deforming the volumetric model on the basis of the difference resulting in a deformed volumetric model.
4. The method of claim 3,
 - wherein the difference is used as a boundary condition for the deformation of the volumetric model.

5. The method of claim 3,

wherein the at least one of shape and position variation of the object of interest is determined on the basis of the deformed volumetric model.

6. The method of claim 3,

wherein a biomechanical model is taken into account for the deformation of the volumetric model.

7. The method of claim 1, wherein the first and second images are computed tomography (CT) images.

8. A radiation therapy planning device, comprising:

a memory for storing a first image and a second image; and

a processor adapted to perform the steps of:

determining a dose distribution for a target volume on the basis of the first image;

determining at least one of shape and position variation of an object of interest in the target volume between the first image and the second image; and

adjusting the dose distribution on the basis of the at least one of shape and position variation;

wherein the first and second images were taken at different points in time of a radiation treatment process.

9. The radiation therapy planning device of claim 8, wherein the processor is further adapted to perform the steps of

applying a first surface mesh to the object of interest in the first image;

performing a first adaptation of the first surface mesh to a surface of the object of interest in the first image resulting in a second surface mesh;

applying the second surface mesh to the object of interest in the second image;

performing a second adaptation of the second surface mesh to the surface of the object of interest in the second image resulting in a third surface mesh;

obtaining a difference between the second surface mesh and the third surface mesh;

generating a volumetric model of the object of interest on the basis of the second surface mesh; and

deforming the volumetric model on the basis of the difference resulting in a deformed volumetric model.

PHUS030326USP

10. The radiation therapy planning device of claim 9,

wherein the difference is used as a boundary condition for the deformation of the volumetric model; and

wherein a biomechanical model is taken into account for the deformation of the volumetric model.

11. A computer program for a radiation therapy planning device, wherein a processor of the radiation therapy device performs the following operation when the computer program is executed on the processor:

- determining a dose distribution for a target volume on the basis of a first image;
- applying a first surface mesh to the object of interest in the first image;
- performing a first adaptation of the first surface mesh to a surface of the object of interest in the first image resulting in a second surface mesh;
- applying the second surface mesh to the object of interest in the second image;
- performing a second adaptation of the second surface mesh to the surface of the object of interest in the second image resulting in a third surface mesh;
- obtaining a difference between the second surface mesh and the third surface mesh;
- generating a volumetric model of the object of interest on the basis of the second surface mesh;
- deforming the volumetric model on the basis of the difference resulting in a deformed volumetric model; and
- adjusting the dose distribution on the basis of the deformed volumetric model;
- wherein the first and second images were taken at different points in time of a radiation treatment process.

Abstract

A method and apparatus for planning a radiation therapy are disclosed. A radiation dose distribution is adapted on the basis of shape and position variations of the organs of interest determined from a comparison of a first image and a second image which were taken at different points of time during the radiation treatment process.

26726.1




FIG 1




Fig. 2